



Product  
Technical  
Data  
Sheet

# ARMOR GUARD

L1300



## *FLOOR FINISH*

A HIGH QUALITY POLYMER FLOOR FINISH. MAY BE USED FOR LOW SPEED SPRAY BUFFING AND HIGH SPEED MAINTENANCE PROGRAMS USING ELECTRIC BURNISHERS AND SYNTHETIC PADS. EXCELLENT LEVELING PROPERTIES MAKE IT EXTREMELY FORGIVING WHEN BEING APPLIED EVEN BY NOVICE USERS. DRIES TO A HIGH INITIAL GLOSS. THIS UNIQUE FORMULA COMBINES COMPONENTS THAT PROVIDE A HIGH GLOSS WHILE EXTENDING THE DURABILITY OF HARD, LOW MAINTENANCE FINISHES WITH THE RESILIENCE AND BURNISHING RESPONSE OF SOFTER, HIGH MAINTENANCE PRODUCTS. PERFECT FOR USE IN LOW MAINTENANCE APPLICATIONS WHERE HIGH DURABILITY IS REQUIRED. AVAILABLE IN 16 AND 20 % SOLIDS.

### FORMULA ADVANTAGES

EXCEPTIONAL LEVELLING

HIGH GLOSS FINISH

MULTI-USE APPLICATIONS

### FORMULA DILUTIONS

APPLY THE FINISH TO A DRY PREVIOUSLY SEALED FLOOR AND ALLOW 30 TO 45 MINUTES DRYING TIME PRIOR TO RECOATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BURNISHED UP TO 3 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS.

### PRODUCT NOTES

CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPERSIBLE WAX RESINS, LEVELLERS AND PLASTISIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE.

### PACKAGING AVAILABILITY

4X4 LITRE CASE

20 LITRE PAIL

115 LITRE MINI DRUM

205 LITRE DRUM

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM