



Product  
Technical  
Data  
Sheet

# MERIT 16

L1301

## *FLOOR FINISH*



A HIGH QUALITY POLYMER FLOOR FINISH. MAY BE USED FOR LOW SPEED SPRAY BUFFING AND HIGH SPEED MAINTENANCE PROGRAMS USING ELECTRIC BURNISHERS AND SYNTHETIC PADS. EXCELLENT LEVELING PROPERTIES MAKE IT EXTREMELY FORGIVING WHEN BEING APPLIED EVEN BY NOVICE USERS. DRIES TO A HIGH INITIAL GLOSS. THIS UNIQUE FORMULA COMBINES COMPONENTS THAT PROVIDE A HIGH GLOSS WHILE EXTENDING THE DURABILITY OF HARD, LOW MAINTENANCE FINISHES WITH THE RESILIENCE AND BURNISHING RESPONSE OF SOFTER, HIGH MAINTENANCE PRODUCTS. PERFECT FOR USE IN LOW MAINTENANCE APPLICATIONS WHERE HIGH DURABILITY IS REQUIRED. AVAILABLE IN 16 AND 20 % SOLIDS.

### FORMULA ADVANTAGES

EXCEPTIONAL LEVELING  
HIGH GLOSS FINISH  
MULTI-USE APPLICATIONS

### FORMULA DILUTIONS

APPLY THE FINISH TO A DRY PREVIOUSLY SEALED FLOOR AND ALLOW 30 TO 45 MINUTES DRYING TIME PRIOR TO RECOATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BURNISHED UP TO 3 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS.  
APPLY

### PRODUCT NOTES

CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPERSIBLE WAX RESINS, LEVELLERS AND PLASTISIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE.

### PACKAGING AVAILABILITY

12X1 LITRE CASE  
4X4 LITRE CASE  
20 LITRE PAIL  
205 LITRE DRUM

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM



Product  
Technical  
Data  
Sheet

**WHITAKER**

# MERIT 20

L1300



## *FLOOR FINISH*

**A HIGH QUALITY POLYMER FLOOR FINISH. MAY BE USED FOR LOW SPEED SPRAY BUFFING AND HIGH SPEED MAINTENANCE PROGRAMS USING ELECTRIC BURNISHERS AND SYNTHETIC PADS. EXCELLENT LEVELING PROPERTIES MAKE IT EXTREMELY FORGIVING WHEN BEING APPLIED EVEN BY NOVICE USERS. DRIES TO A HIGH INITIAL GLOSS. THIS UNIQUE FORMULA COMBINES COMPONENTS THAT PROVIDE A HIGH GLOSS WHILE EXTENDING THE DURABILITY OF HARD, LOW MAINTENANCE FINISHES WITH THE RESILIENCE AND BURNISHING RESPONSE OF SOFTER, HIGH MAINTENANCE PRODUCTS. PERFECT FOR USE IN LOW MAINTENANCE APPLICATIONS WHERE HIGH DURABILITY IS REQUIRED. AVAILABLE IN 16 AND 20 % SOLIDS.**

### FORMULA ADVANTAGES

**EXCEPTIONAL LEVELING**

**HIGH GLOSS FINISH**

**MULTI-USE APPLICATIONS**

### FORMULA DILUTIONS

**APPLY THE FINISH TO A DRY PREVIOUSLY SEALED FLOOR AND ALLOW 30 TO 45 MINUTES DRYING TIME PRIOR TO RECOATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BURNISHED UP TO 3 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS.**  
**APPLY**

### PRODUCT NOTES

**CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPERSIBLE WAX RESINS, LEVELLERS AND PLASTISIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE.**

### PACKAGING AVAILABILITY

**4X4 LITRE CASE**

**20 LITRE PAIL**

**205 LITRE DRUM**

## **S.J. WHITAKER INDUSTRIES INC.**

16632 - 117 Ave. Edmonton, Alberta, Canada T5M 3W2

• Toll Free: 1-800-665 - CHEM (2436)•

• (780) 451-2998 • Fax: (780) 455-8252 • Visit our website: [www.whitchem.com](http://www.whitchem.com)•