




Product  
Technical  
Data  
Sheet

# IMAGE 20

L1304

## *FLOOR FINISH*



**THIS PRODUCT HAS EXCEPTIONAL LEVELING PROPERTIES AND FAST RECOATABILITY. MAY BE USED WITH EITHER LOW SPEED OR HIGH SPEED MAINTENANCE PROGRAMS. MAINTAINS AN EXCEPTIONAL HIGH GLOSS AND CAN BE BURNISHED DAILY OR ON AN INTERMITTENT SCHEDULE. IDEAL FOR USE IN HIGH MAINTENANCE PROCEDURES WHERE HIGH GLOSS IS DESIRED. HAS VERY GOOD RESISTANCE AND DURABILITY. AVAILABLE IN 16 AND 20 % SOLIDS.**

### FORMULA ADVANTAGES

**EXCEPTIONAL LEVELING**

**HIGH GLOSS FINISH**

### FORMULA DILUTIONS

**FLOORS MUST BE PROPERLY PREPARED BEFORE APPLICATION. STRIP OLD FINISH, RINSE WELL AND NEUTRALIZE SURFACE. APPLY TWO THIN, EVEN COATS OF FINISH USING A FRESH CLEAN, HARD STRING MOP. ALLOW 45-60 MINUTES IN BETWEEN COATS.**

### PACKAGING AVAILABILITY

**4X4 LITRE CASE**

**20 LITRE PAIL**

**205 LITRE DRUM**

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

**WHITAKER** INDUSTRIES.COM