



Product
Technical
Data
Sheet

IMAGE 16

L1305



FLOOR FINISH

THIS PRODUCT HAS EXCEPTIONAL LEVELING PROPERTIES AND FAST RECOATABILITY. MAY BE USED WITH EITHER LOW SPEED OR HIGH SPEED MAINTENANCE PROGRAMS. MAINTAINS AN EXCEPTIONAL HIGH GLOSS AND CAN BE BURNISHED DAILY OR ON AN INTERMITTENT SCHEDULE. IDEAL FOR USE IN HIGH MAINTENANCE PROCEDURES WHERE HIGH GLOSS IS DESIRED. HAS VERY GOOD RESISTANCE AND DURABILITY. AVAILABLE IN 16 AND 20 % SOLIDS.

FORMULA ADVANTAGES

EXCEPTIONAL LEVELING

HIGH GLOSS FINISH

FORMULA DILUTINS

FLOORS MUST BE PROPERLY PREPARED BEFORE APPLICATION. STRIP OLD FINISH, RINSE WELL AND NEUTRALIZE SURFACE. APPLY TWO THIN, EVEN COATS OF FINISH USING A FRESH CLEAN, HARD STRING MOP. ALLOW 45-60 MINUTES IN BETWEEN COATS.

PACKAGING AVAILABILITY

**4X4 LITRE CASE
20 LITRE PAIL
205 LITRE DRUM**

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM