



Product
Technical
Data
Sheet

EURO

L1307



FLOOR FINISH

A URETHANE FORTIFIED POLYMER FINISH. PROVIDES ALL THE ADVANTAGES OF AN ALL-ACRYLIC SYSTEM INCLUDING EXCELLENT LEVELING, EASE OF APPLICATION AND REMOVAL WHILE PROVIDING THE INCREASED RESISTANCE TO HARSH, DEMANDING CONDITIONS. DRIES TO AN EFFECTIVE HIGH GLOSS FINISH. PROVIDES A SHIELD-LIKE FINISH ON THE FLOOR TO RESIST SCRATCHING AND MARKING. MAY BE USED ON ALL TYPES OF FLOORS AND IS EASILY MAINTAINED.

FORMULA ADVANTAGES

URETHANE FORTIFIED

MAY BE USED ON ALL FLOOR SURFACES

HIGH GLOSS FINISH

FORMULA DILUTIONS

APPLY THE FINISH TO A DRY PREVIOUSLY SEALED FLOOR AND ALLOW 30 TO 45 MINUTES DRYING TIME PRIOR TO RECOATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BUFFED OR BURNISHED UP TO 3 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS. FOR STRIPPING USE TOUGH STRIP (L1324) AT A DILUTION OF 1:7.

PRODUCT NOTES:

IT CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPERSIBLE WAX RESINS, URETHANE, LEVELLERS AND PLASTISIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE.

PACKAGING AVAILABILITY

4X4 LITRE CASE

20 LITRE PAIL

205 LITRE DRUM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM