




Product  
Technical  
Data  
Sheet

# WOOD FLOOR FINISH L1309



## DESCRIPTION

THIS IS A TOP OF THE LINE, URETHANE FORTIFIED, HIGHLY RESILIENT FLOOR FINISH. IT REQUIRES VERY LITTLE WORK TO MAINTAIN ITS DEEP, LUSTROUS GLOSS. SCRATCH AND SCRUFF RESISTANT, THE SHINE CAN BE EASILY RESTORED WITH BUFFING AND BURNISHING. THIS FINISH IS ESPECIALLY DESIGNED FOR GYMNASIUM WOOD FLOORS.

## DIRECTIONS

APPLY THE FINISH TO A DRY PREVIOUSLY SEALED FLOOR AND ALLOW 30 TO 45 MINUTES DRYING TIME DEPENDING UPON HUMIDITY PRIOR TO RECOATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BUFFED OR BURNISHED UP TO 3 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS. COVERAGE AREA 1800-2400 SQ. FT./GAL. DEPENDING UPON THICKNESS OF APPLICATION.

## PROPERTIES

IT CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPERSIBLE WAX RESINS, URETHANE, LEVELLERS AND PLASTISIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE.

## PACKAGING AVAILABILITY

4X4 LITRE CASE  
20 LITRE PAIL

WHITAKER INDUSTRIES.COM

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6  
Toll Free: 1-800-665 - CHEM (2436)  
(780) 419-2910 Fax: (780) 419-2169