




Product
Technical
Data
Sheet

CONCRETE SEALER L1312



DESCRIPTION

CONCRETE SEALER CAN BE APPLIED ON TROWELED CONCRETE TO CONTROL DUSTING AND PROVIDE RESISTANCE TO SOME COMMON INDUSTRIAL CHEMICALS. *CONCRETE SEALER* POSSESSES ADHESION AND CHEMICAL RESISTANCE QUALITIES NECESSARY TO HOLD UP UNDER ABUSIVE CONDITIONS.

DIRECTIONS

TO ASSURE GOOD PERFORMANCE AND ADHESION PROPERTIES, FLOORS SHOULD BE THOROUGHLY CLEANED BEFORE APPLICATION. RESIDUAL OIL OR GREASE ON THE SURFACE CAN AFFECT PERFORMANCE PROPERTIES OF THE COATING.

USE AS A SEALER COAT ON INTERIOR CONCRETE SURFACES. THREE OR MORE COATS PER APPLICATION ARE SUGGESTED AND MAY BE APPLIED WITH 30-45 MIN. DRYING TIME DEPENDING ON SOLIDS AND CONDITIONS.

PACKAGING AVAILABILITY

4X4 LITRE CASE
20 LITRE PAIL
205 LITRE DRUM

WHITAKER
INDUSTRIES.COM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169