



Product
Technical
Data
Sheet

IMPRESS

L1313

FLOOR FINISH



DESCRIPTION

THIS PRODUCT PROVIDES OUTSTANDING DURABILITY AND LONG LASTING HIGH GLOSS. IMPRESS HAS A RAPID MULTI-COATING ABILITY WHICH MAKES IT EASY TO WORK WITH. IT ALSO OFFERS EXCELLENT BLACKHEEL MARK RESISTANCE AND THE ABILITY TO BE BURNISHED WITH HIGH SPEED PROPANE.

PROPERTIES

IT CONTAINS A METAL CROSS LINKED ACRYLIC POLYMER, DISPENSIBLE WAX RESINS, LEVELERS AND PLASTICIZERS. IT WAS DESIGNED FOR EASY APPLICATION AND MAINTENANCE WITH A HIGH SPEED MAINTENANCE PROGRAM.

DIRECTIONS

APPLY THE FINISH TO A DRY, PREVIOUSLY SEALED FLOOR AND ALLOW 20 TO 30 MINUTES DRYING TIME PRIOR TO RE-COATING. APPLY 3 TO 4 COATS AND LET DRY THOROUGHLY BEFORE BURNISHING. IT CAN BE BURNISHED 3 TO 5 TIMES WEEKLY TO RESTORE THE ORIGINAL DEEP GLOSS.

PACKAGING AVAILABILITY

**4X4 LITRE CASE
20 LITRE PAIL
205 LITRE DRUM**

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM