



Product
Technical
Data
Sheet

AQUATREAT 410

L5201



BOILER DESCALER

A CONCENTRATED SCALE AND CORROSION PREVENTATIVE BOILER WATER COMPOUND, FORMULATED SPECIFICALLY FOR USE IN THE OIL PATCH. IT IS A NON-FREEZABLE, HIGHLY ALKALINE SOLUTION CONTAINING CORROSION INHIBITORS AND DISPERSANTS.

DIRECTIONS

FOR INITIAL TREATMENT USE 1 PART TO 2000 PARTS OF WATER IN THE SYSTEM. ADD MORE BOILER COMPOUND EVERY 12 HOURS TO MAKE UP WATER. BLOW DOWN THE BOILER REGULARLY BEFORE ADDING THE BOILER COMPOUND. CHECK THE pH OF THE BOILER WATER DAILY. IT SHOULD BE KEPT IN THE RANGE OF 10.5 TO 11. THE BOILER SHOULD BE INSPECTED ANNUALLY AND PROPERLY CLEANED AND DESCALED. PERIODICALLY SUBMIT A SAMPLE OF THE BOILER WATER TO YOUR SUPPLIER FOR A MORE COMPLETE ANALYSIS. SAMPLES SHOULD BE TAKEN BEFORE BLOW DOWN, BUT ALLOW A FEW GALLONS TO PASS THROUGH BEFORE TAKING THE SAMPLE.

CAUTION

THIS IS A HIGHLY ALKALINE PRODUCT. KEEP OUT OF THE REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES.

PRODUCT AVAILABILITY

20 LITRE PAIL
205 LITRE DRUM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6
Toll Free: 1-800-665 - CHEM (2436)
(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM