



Product  
Technical  
Data  
Sheet

# AQUATREAT 200

L5202



## *BOILER COMPOUND*

A BALANCED LIQUID BOILER WATER TREATMENT FOR HOT WATER BOILERS AND CLOSED SYSTEMS. PREVENTS SCALE FROM FORMING AN INSULATING BARRIER. KEEP SOLIDS IN SUSPENSION TO BE ELIMINATED BY BLOWING DOWN THE SYSTEM. A CONCENTRATED BALANCE OF CORROSION INHIBITORS, OXYGEN SCAVENGERS, DISPERSANTS AND CHELATING AGENTS PROTECT SYSTEM AGAINST RUSTING, PITTING AND CORROSION.

### FORMULA ADVANTAGES

CONCENTRATED FORMULA

### FORMULA DILUTIONS

- 1) TEST HARDNESS OF FEED WATER. HARDNESS SHOULD NOT BE HIGHER THAN 200 ppm.
- 2) ESTIMATE THE AMOUNT OF WATER IN BOILER.
- 3) FOR INITIAL TREATMENT, ADD 1 GALLON OF *AQUATREAT 200* FOR EACH 200 GALLONS OF MAKE-UP WATER.
- 4) USE APPROXIMATELY 1 GALLON OF *AQUATREAT 200* TO 500 GALLONS OF MAKE-UP WATER.
- 5) BLOWDOWN AT LEAST 10 % OF BOILER WATER PER DAY.
- 6) CHECK PH OF WATER DAILY. IF BELOW 10, INCREASE TREATMENT BY 10 %
- 7) FOR A MORE DETAILED ANALYSIS, SUBMIT A SAMPLE OF BOILER WATER TO YOUR SUPPLIER PERIODICALLY. SAMPLES SHOULD BE TAKEN BEFORE BLOWDOWN. A FEW GALLONS SHOULD BE TAKEN BEFORE BLOWDOWN. A FEW GALLONS SHOULD BE TAKEN BEFORE TAKING THE SAMPLE.

### PRODUCT NOTES:

THIS IS AN ALKALINE PRODUCT. KEEP OUT OF REACH FROM CHILDREN. AVOID CONTACT WITH SKIN OR EYES.

### PACKAGING AVAILABILITY

20 LITRE PAIL  
205 LITRE DRUM

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6  
Toll Free: 1-800-665 - CHEM (2436)  
(780) 419-2910 Fax: (780) 419-2169

INDUSTRIES.COM  
**WHITAKER**