



Product
Technical
Data
Sheet

AQUATREAT 205

L5205



BOILER COMPOUND

A CONCENTRATED BALANCED BOILER COMPOUND FOR TREATMENT OF WATER BOILERS AND CLOSED SYSTEMS OPERATING AT PRESSURES OF LESS THAN 900 PSI. IT CONTAINS CHELATING AGENTS, PHOSPHATE, DISPERSANTS, NITRITE AND OTHER CORROSION INHIBITORS.

DIRECTIONS

TEST HARDNESS OF FEED WATER. HARDNESS SHOULD NOT BE HIGHER THAN 200 PPM. IF HARDNESS EXCEEDS 200 PPM, A SEPARATE SOFTENING PROCEDURE SHOULD BE IMPLEMENTED.

FOR INITIAL TREATMENT, ADD 1 PART OF AQUATREAT 205 TO 200 PARTS OF WATER IN THE SYSTEM. ADD AQUATREAT 205 AT A RATE OF APPROXIMATELY 1:500 PARTS OF MAKE UP WATER. THE MORE MAKE UP WATER IS ADDED THE MORE FREQUENTLY THE BOILER SHOULD BE BLOWN DOWN.

PRODUCT NOTES

THIS IS AN ALKALINE PRODUCT. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES. THIS PRODUCT SHOULD NOT BE USED IN SYSTEMS WHERE FOOD IS PROCESSED.

PACKAGING AVAILABILITY

20 LITRE PAIL
205 LITRE DRUM

WHITAKER INDUSTRIES.COM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169