



Product
Technical
Data
Sheet

AQUATREAT 800

L5206



COOLING TOWER SANITIZER

A MIXTURE OF A DISPERSANT BLEND, CORROSION INHIBITOR AND NEUTRALIZING AMINES WHICH PROVIDE A COMPLETE STEAM BOILER TREATMENT.

FOR USE IN SYSTEMS THAT HAVE A VERY HIGH RATE OF RETURNED STEAM CONDENSATE AND HAVE FEW REQUIREMENTS FOR ADDITIONAL RAW FEED WATER.

MAY BE AUGMENTED BY AMINE TREATMENTS WHERE OVERHEAD OR STEAM LINE CORROSION IS REQUIRED.

DIRECTIONS

INITIALLY, IT SHOULD BE FED INTO THE STEAM BOILER AT A 1:2000 RATIO (PRODUCT TO BOILER WATER).

TREATMENT LEVEL IN THE BOILER WATER IS EASILY MONITORED BY TESTING FOR MOLYBDENUM AND ADDING ADDITIONAL TREATMENT AS NEEDED TO MAINTAIN A MOLYBDENUM RESIDUAL OF 100 PPM. AMOUNTS NEEDED WILL DEPEND ON WATER QUALITY AND CONCENTRATIONS. IT IS RECOMMENDED THAT THE TOTAL DISSOLVED SOLIDS BE PERIODICALLY CHECKED TO ENSURE THE BOILER WATER DOES NOT CONCENTRATE TO EXCESSIVELY HIGH LEVELS.

PRODUCT NOTES:

CONCENTRATED PRODUCT IS CORROSIVE TO ALUMINUM, ZINC, MAGNESIUM, AND OTHER SOFT ALLOYS. DO NOT ALLOW PRODUCT TO FREEZE. PRODUCT MAY BECOME PERMANENTLY DAMAGED OR CRYSTALS MAY FORM WHICH WILL NOT DISSOLVE READILY AT ROOM TEMPERATURE.

PACKAGING AVAILABILITY

20 LITRE PAIL
205 LITRE DRUM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6
Toll Free: 1-800-665 - CHEM (2436)
(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM