



Product
Technical
Data
Sheet

AQUATREAT 100

L5271

BOILER COMPOUND



DESCRIPTION

A CONCENTRATED LIQUID WATER SOFTENING AND DEGREASING DETERGENT DESIGNED FOR CLEANING BOILERS AND NEUTRALIZING THE CHEMICAL RESIDUE AFTER DESCALING.

THIS PRODUCT HAS BEEN DESIGNED TO EMULSIFY AND REMOVE GREASY, OILY RESIDUE OFTEN FOUND IN NEW BOILERS AFTER INSTALLATIONS. THESE OILS AND GREASES CAN CAUSE DISRUPTIVE FOAMING AND SURGING. AFTER PROPER WASHING WITH THIS PRODUCT, BOILERS WILL PERFORM SMOOTHLY AND EFFICIENTLY. AFTER CLEANING, DRAIN BOILER AND RESUME NORMAL SERVICE AND BOILER TREATMENT PROGRAMS.

DIRECTIONS

FOR STEAM BOILERS - BOILER SHOULD BE FILLED WELL ABOVE NORMAL OPERATING LEVEL. ADD 1 PART TO 10 PARTS OF WATER IN SYSTEM. RAISE BOILER TEMPERATURE TO BETWEEN 60 TO 70 DEGREES C. ALLOW BOILER TO OPERATE FOR 2 TO 4 HOURS. VERY HEAVY DEPOSITS OF GREASE OR OIL MAY REQUIRE LONGER OPERATION AND INCREASED TEMPERATURE. AFTER DRAINING, RINSE WITH FRESH WATER AND RETURN TO NORMAL SERVICE. FOR HOT WATER RECIRCULATING SYSTEMS - ADD 1 PART TO 10 PARTS OF WATER IN SYSTEM AND CIRCULATE FOR 24 HOURS. THEN BLEED OFF WATER UNTIL BLEED WATER IS PERFECTLY CLEAR. ONCE SYSTEM IS COMPLETELY CLEANED OF ANY RESIDUE, ADD NORMAL BOILER TREATMENT.

PACKAGING AVAILABILITY

20 LITRE PAIL
115 LITRE MINI DRUM
205 LITRE DRUM

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6
Toll Free: 1-800-665 - CHEM (2436)
(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM