



Product  
Technical  
Data  
Sheet

# AQUATREAT 105

L5272



## *BOILER COMPOUND*

**A HIGHLY CONCENTRATED NON-FOAMING, NON-CHLORINATED ALKALI BASED CLEANER USED TO RAPIDLY AND EFFECTIVELY REMOVE PAINT, RUST, GREASE, BUFFING COMPOUNDS, CARBONIZED DEPOSITS, SILICA AND MANY OTHER MATERIALS FROM FERROUS AND STEEL METAL SURFACES.**

### **DIRECTIONS**

#### ***FOR CIRCULATION CLEANING***

**USE A 1-2% SOLUTION AT 140-160°F AND CIRCULATE FOR AT LEAST 30 MINUTES.**

#### ***FOR DIP TANKS***

**USE A 2-3% SOLUTION AT 150-180°F.**

#### ***FOR BOIL OUT OPERATION***

**USE A 4-5% SOLUTION AT 180-200°F**

**DO NOT USE ON ALUMINUM, ZINC, GALVANIZED METALS OR PAINTED SURFACES.**

### **CONTAINS**

**SODIUM HYDROXIDE, WATER, SODIUM GLUCONATE AND PHOSPHONATES.**

**SODIUM HYDROXIDE, SOLUTION UN 1824**

### **PACKAGING AVAILABILITY**

**20 LITRE PAIL**

**205 LITRE DRUM**

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

**WHITAKER** INDUSTRIES.COM