



Product  
Technical  
Data  
Sheet

# DECLOG DRY

P2010



## *DRAIN OPENER*

**DECLOG DRY IS DESIGNED TO DISSOLVE GREASE AND OTHER ORGANIC MATTER THAT CLOGS UP SEWER LINES, DRAIN LINES AND GREASE TRAPS. IT CONTAINS A SPECIAL INHIBITOR TO PREVENT DAMAGE TO IRON PIPING AND WILL NOT HARM PLASTIC OR CONCRETE PIPES.**

### DIRECTIONS

**USE *DECLOG DRY* AS REQUIRED. FOR SINK DRAINS, APPLY 1 CUP DIRECTLY AND ALLOW 20 MINUTES, REPEAT IF NECESSARY. FOR LARGER DRAINS, USE 1 TO 3 CUPS. IF BLOCKAGE REMAINS AFTER REPEATED APPLICATIONS, USE A MECHANICAL CLEANING METHOD TO OPEN LINE. APPLY 1 CUP OF *DECLOG DRY* TO DRAIN WEEKLY TO MAINTAIN CLEAR LINES.**

### PRECAUTION

**CONTAINS SODIUM HYDROXIDE. AVOID CONTACT WITH SKIN, EYES, OR CLOTHING. IF CONTACT IS MADE WITH EYES, RINSE THOROUGHLY WITH COLD WATER AND SEEK MEDICAL ATTENTION.**

### PACKAGING AVAILABILITY

**10 KG PAIL  
20 KG PAIL**

**WHITAKER** INDUSTRIES.COM

## **S.J. WHITAKER INDUSTRIES INC.**

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6  
Toll Free: 1-800-665 - CHEM (2436)  
(780) 419-2910 Fax: (780) 419-2169