



Product
Technical
Data
Sheet

SILVER PRESOAK

P2262



SILVERWARE PRESOAK

A NON-CHLORINATED GRANULAR PRESOAK DESIGNED TO DETARNISH SILVERWARE AND TO LIFT HARD TO REMOVE SOILS FROM CUTLERY AND DINNERWARE.

FORMULA ADVANTAGES

REMOVES STAINS

FORMULA DILUTIONS

AS A PRESOAK, ADD PRODUCT TO HOT WATER (140 DEG. F) AT A CONCENTRATION OF 1 TO 3 OZ. PER GALLON OF WATER. ALLOW CUTLERY TO SOAK FOR 5 TO 30 MINUTES OR UNTIL THE SOIL HAS BECOME SOFT AND EASY TO REMOVE. RINSE WELL BEFORE WASHING THESE ITEMS IN DISHWASHER. FOR THE REMOVAL OF TARNISH, USE 1 TO 3 OZ. PER GALLON OF HOT WATER. BE SURE ALL SILVER PIECES ARE IN CONTACT WITH ALUMINUM FOIL. AN ELECTROLYTIC PROCESS WILL TAKE PLACE WHICH WILL LOOSEN AND LIFT TARNISH FROM SILVERWARE. WHEN REMOVING TARNISH FROM STAINLESS STEEL KNIVES, BE SURE BLADES DO NOT CONTACT ALUMINUM TANK OR FOIL DAMAGE CAN OCCUR TO BOTH BLADE AND TANK.

PACKAGING AVAILABILITY

10 KG PAIL

20 KG PAIL

S.J. WHITAKER INDUSTRIES INC.

15 CALDER PLACE, ST. ALBERT, AB T8N 5A6

Toll Free: 1-800-665 - CHEM (2436)

(780) 419-2910 Fax: (780) 419-2169

WHITAKER INDUSTRIES.COM